



ESAB Cutmaster 40

Portable Inverter Plasma Cutting Equipment



ESAB Cutmaster 40

Portable and Versatile

The ESAB Cutmaster 40 is designed to cut all day at its recommended cutting capacity. The equipment weighing 12 kgs is one of the lightest in its class. The equipment is best suited to operate on 230V, but can also be used with 110V supply.

- True Cut™ – 12mm
- TD Surelok® technology for better quality cuts and longer parts life
- Automatic input voltage selection between 110 / 230V
- Lightweight design for maximum portability

Visit www.esabindia.com for more information.

Application Areas

- Repair and Maintenance
- HVAC (Heating, Ventillation & Air-conditioning)
- Railways
- Stainlees steel Furniture & Decorative products



Specifications / Technical Data

Power Source	ESAB Cutmaster 40 (230V)	ESAB Cutmaster 40 (110V)
Mains supply, V/Ph, Hz	230 ± 10% / 1, 50/60	120 ± 10% / 1, 50/60
Output current range, A	20 – 40	20 – 27
Output current , A / Duty cycle	40 / 40%	30 / 30%
Enclosure class	IP23C	
Weight, Kg	11.8	
Dimensions, l x w x h, mm	117 x 228 x 470	
True Cut™(Recommended cut), mm	12	6
Maximum cut, mm	22	15
Pierce cut, mm	8	6
Manual Cutting Torch	SL60	
Torch Length, m	6.1	
Torch air pressure, bar	5.2	
Torch air consumption, l/min	190	

Ordering Information

Description	Part Number
ESAB Cutmaster 40, SL60 1Torch™ 6.1m	0559142460
ATC® 1Torch® SL 60 75° 6.1m	7-5204
Note : ESAB Cutmaster 40 is delivered with 6.1m SL60 1Torch™, work cable, clamp and power cable	

Ordering Information – Wear and Spare Parts

Description	Part Number	Description	Part Number
Electrode CM 40/100	9-8215	Drag Cutting & Gouging	
Start Cartridge CM 40/100	9-8213	Shield Cup Body Drag CM 40/100	9-8237
Standoff Cutting		Drag Cutting	
Shield Cup CM 40/100	9-8218	Tip – Drag (40A) CM 40	9-8207
Tip – Standoff (40A) CM 40	9-8208	• Shield Cap Drag CM 40	9-8244
Standoff Cutting Guide (40A)	9-8251	• Torch Deflector CM 40/100	9-8243
		Gouging	
		Tip – Gouging (40A) CM 40	9-8225
		Shield Cap Gouging CM 40/100	9-8241
Note : Please select Tip depending on application, shield cup drag has to be used with torch deflector / shield cap.			

Eastern Regional Office
P41 Taratala Road
Kolkata 700 088
Tel : (033) 2401 9671
Fax : (033) 2401 4427
Email : eqptsales.er@esab.co.in

Western Regional Office
501/502, 5th Floor, Sagar Tech-B
Andheri Kurla Road, Saki Naka
Andheri East, Mumbai 400 072
Tel : (022) 2851 7386
Fax : (022) 2852 4974
Email : eqptsales.wr@esab.co.in

Northern Regional Office
239 – 240, DLF Tower
Shivaji Marg, Near Karampura
Crossing, New Delhi 110 015
Tel : (011) 4142 7091
Fax : (011) 4142 7099
Email : eqptsales.nr@esab.co.in

Southern Regional Office
13, Industrial Estate, III Main Road,
Ambattur, Chennai – 600 058
Tel : (044) 4295 7894 / 95
Fax : (044) 4295 7889
Email : eqptsales.sr@esab.co.in

Central Regional Office
No. 218, Ashirvad
South Ambazari Road
Bajaj Nagar, Nagpur 440 010
Tel : (0712) 222 9547 / 48
Fax : (0712) 222 9549
Email : eqptsales.cr@esab.co.in



ESAB / esabindia.com

Regd & H. O. : ESAB INDIA LIMITED
13, Industrial Estate, III Main Road
Ambattur, Chennai – 600 058
Email: info@esab.co.in



COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV
= ISO 9001 =
= ISO 14001 =
= OHSAS 18001 =